



AUTOMATIC LUBRICATION SYSTEM

CARTLUBERR

Why Automatic Lubrication is required ?

Automatic Lubrication System Provide the required Lubricants at proper Time & Precise Quantity. This ensures



- There is no wastage of lubricants (excess application)
- Separate maintenance of machine weared out parts are neglected.
- Machine down time is reduced



CARTLUBERR is a multipoint Electrically Operated grease pump.



Pump can deliver grease to max 3 points directly without any dividing accessories.



12VDC/24VDC motor as the maindrive motors to run the pumps.



Stirrer assembly to feed the grease into pumping units



A P P L I C A T I O N S

RIKKON GROUP OF COMPANIES





Technical Pump Specifications

Reservoir capacity : 1KG

Operating Voltage: DC 12V / 24V

Max. No. of outlets : 3

Working Pressure : 250bar

Max. grease capability : NLGI grade 2

Operating Temperature : -25 deg c - +80 deg c

Storage Temperature : -30 deg c - +90 deg c

Noise : < 70 db (A)

Pumping unit specification

Pumping unit variants

0.2CC/stroke

0.35CC/stroke

Mounting Thread:M22X1.5

Outlet Thread:M10X1



cartridges available ,

NLG 000 (SA 628)

NLGI 00 (SA 629)

NLG 10 (SA 630)

NLGI 1 (SA 631)

Note: codes inside the brackets are the part number.

contact us



📍 No: 203, Nageswara Rao Road, 2nd extn.,
Athipet, Ambattur, Chennai - 600 058
Tamil Nadu, INDIA

✉️ info@rikkongroup.com / sales@rikkongroup.com
🌐 www.rikkongroup.com / www.luberr.in



contact person :