



SVM 11

SINGLE LINE GREASE INJECTOR

GENERAL OPERATIONAL INFORMATION

The LUBERR Grease Injector Model SVM 11 can dispense large output quantity. And SVM 11 operates with lubricant up to Grease Grade NLGI-1. The SVM 11 Grease Injector has manual adjuster for optimizing the output quantity as per actual bearing requirements.

The LUBERR SVM 11 Grease Injectors can be installed individually or combined using a manifold with feed line supplying to the bearing point.

The SVM 11 Grease injectors can be used in the system along with SVM 33 , SVM 32 and SVM 01 Injectors.

- Easy Lubricant output manual adjuster
- Visual Indication pin is provided for inspecting Injector working.
- External greasing optional port provided for use in case of Injector failure.
- The optional port can also be used to fill feed lines during installations.
Suitable for +93 Deg C max Temperature application.



TECHNICAL SPECIFICATIONS

Lubricant Output Min	0.82 cc (0.05 Cu. In.)	Inlet Connection	1/2" NPTF
Lubricant Output Max	8.19 cc (0.50 Cu. In.)	Outlet Connection	1/8" NPTF or 1/4" NPTF
Min Operating Pressure	90 Bars (1250 PSI)	Monitoring	Cycle indicator
Max Operating Pressure	230 Bars (3500 PSI)	Lubricant	Max upto NLGI grade 2
Vent Pressure	55 Bars (800 PSI)		

contact us



No: 203, Nageswara Rao Road, 2nd extn.,
Athipet, Ambattur, Chennai - 600 058
Tamil Nadu, INDIA

info@rikkongroup.com / sales@rikkongroup.com
www.rikkongroup.com / www.luberr.in



contact person :