

SVM 34 INJECTORS

LUBERR SVM 34 are metering type flow-rate output injectors used for centralized oil and soft grease lubrication system with Manual, pneumatic or motorized Pumps. They can be installed on one-side or two-side manifolds or directly on the lubrication points.



How to Order ?

SVM - 34 - X - X - X

MATERIAL

- 1 - SS
- 2 - BRASS

OUTPUT THREAD

- 1 - M8 X 1P
- 2 - R 1/8

FLOW RATE

- 1 - FLOW RATE - 1
- 2 - FLOW RATE - 2
- 3 - FLOW RATE - 4
- 4 - FLOW RATE - 8
- 5 - FLOW RATE - 16

Technical specification

Model | SVM 34

Inlet Thread | M8X1P

Outlet Thread | M8X1P or 1/8" BSP

Flow Rate | 1, 2 , 3 , 4 & 5

Use Oil Viscosity | Oil 50 to 500 cSt @40°C

contact us



📍 No: 203, Nageswara Rao Road, 2nd extn.,
Athipet, Ambattur, Chennai - 600 058
Tamil Nadu, INDIA

✉️ info@rikkongroup.com / sales@rikkongroup.com
🌐 www.rikkongroup.com / www.luberr.in

contact person :

