



AUTOMATIC LUBRICATION SYSTEM

HYDRALUBERR HYDRAULIC GREASE PUMP

GENERAL OPERATIONAL INFORMATION

Luberr Grease Pump model hydraluberr is an hydraulic operated grease pump or transfer pump to dispense lubricant NLGI 2.

The total quantity required for the equipment to be lubricated should not exceed the pump output capacity. This pump is used for a centralised single line parallel system connected using injectors.

Specifications :

TYPE : HYDRALUBERR (INJECTOR MODEL)

NO OF OUTLET : 1

OPERATING TYPE : HYDRAULIC OPERATED

MODEL NUMBER : HYD-40-I

LUBRICANT OUTPUT : 400 - 420 GMS/MIN VARIES WITH LUBRICANT
CONSISTENCY

MAX. OPERATING PRESSURE : 350BAR MAX

RESERVOIR CAPACITY : 40KG

INLET OIL PRESSURE : 60BAR

INLET OIL FLOW SET AT : 10LPM

OUTLET PORT THREAD : 1/2" BSP

CHARGING PORT : 3/8" QRC

LUBRICANT USED : GREASE UPTO NLGI GRADE 2

PRV SET AT : 200 (+10) BAR

VENT VALVE : ELECTRIC OPERATED 24VDC



contact us



📍 No: 203, Nageswara Rao Road, 2nd extn.,
Athipet, Ambattur, Chennai - 600 058
Tamil Nadu, INDIA

✉️ info@rikkongroup.com / sales@rikkongroup.com
🌐 www.rikkongroup.com / www.luberr.in



contact person :